


circuit-breakers with residual current trip (CBR)

mod. pack. Article No. EAN
widths units (4014712...)

Type B



circuit-breakers with residual current trip DFL 8 B SK



AC/DC-sensitive Type B, increased surge current strength

DFL 8 100-4/0,03-B SK	100 A, $I_{\Delta n} = 0.03$ A	1	09164784	153691
DFL 8 125-4/0,03-B SK	125 A, $I_{\Delta n} = 0.03$ A	1	09174784	153707
DFL 8 160-4/0,03-B SK	160 A, $I_{\Delta n} = 0.03$ A	1	09184784	153714
DFL 8 200-4/0,03-B SK	200 A, $I_{\Delta n} = 0.03$ A	1	09204784	153721
DFL 8 250-4/0,03-B SK	250 A, $I_{\Delta n} = 0.03$ A	1	09214784	153738


0-150 kHz, $I_{\Delta n} 0.03$ A, function range for test device 50-400 V, adjustment range for overload trip $0.8-1 \times I_n$, adjustment range for short-circuit trip $6-10 \times I_n$

Accessories: housing N-7
on Page: [61](#)

Type B



circuit-breakers with residual current trip DFL 8 B SK V



AC/DC-sensitive Type B, increased surge current strength

DFL 8 160-4/0,03-B SK V500	160 A	1	09184774	217195
DFL 8 200-4/0,03-B SK V500	200 A	1	09204774	237865


0-150 kHz, $I_{\Delta n} 0.03$ A, non-response lag time t_v adjustable 60/150/300/450 ms, adjustment range for overload trip $0.8-1 \times I_n$, adjustment range for short-circuit trip $6-10 \times I_n$, function range for test device 50 V - 550 V

Accessories: housing N-7
on Page: [61](#)

Type B



circuit-breakers with residual current trip DFL 8 B SK X



AC/DC-sensitive Type B, increased surge current strength

DFL 8 100-4/X-B SK	100 A	1	09169784	153547
DFL 8 125-4/X-B SK	125 A	1	09179784	153554
DFL 8 160-4/X-B SK	160 A	1	09189784	153561
DFL 8 200-4/X-B SK	200 A	1	09209784	153578
DFL 8 250-4/X-B SK	250 A	1	09219784	153585


0-150 kHz, $I_{\Delta n}$ adjustable 0.3-0.5-1.0 A, non-response lag time t_v adjustable 60/150/300/450 ms (adjustable), adjustment range for overload trip $0.8-1 \times I_n$, adjustment range for short-circuit trip $6-10 \times I_n$, function range for test device 50 V - 440 V

Accessories: housing N-7
on Page: [61](#)

Type B



circuit-breakers with residual current trip DFL 8 B SK X V



AC/DC-sensitive Type B, increased surge current strength

DFL 8 200-4/X-B SK V500	200 A	1	09209774	236783
DFL 8 250-4/X-B SK V500	250 A	1	09219774	209657

0-150 kHz, $I_{\Delta n}$ adjustable 0.3-0.5-1.0 A, non-response lag time t_v adjustable 60/150/300/450 ms (adjustable), adjustment range for overload trip $0.8-1 \times I_n$, adjustment range for short-circuit trip $6-10 \times I_n$, function range for test device 50 V - 550 V

Accessories: housing N-7
on Page: [61](#)

Accessories

housing N-7



For circuit-breakers with residual current trip DFL 8

housing N-7	1	09200028	075412
-------------	---	--------------------------	--------

IP54, lockable, bracket diameter max. 6 mm